

OIL FLOW METER

Oval Gear Flow Meter



ASP-E- 25 - 40 - 50 Aluminum Oval Gear Meter With Electronic Register

Aluminum oval gear meter has the ability to handle a wide range of fluid viscosities, with exceptional levels of repeatability and durability, applying in the petroleum, chemical, food industry, etc.

Quick Features :

- High Accuracy, LCD Display
- Compact Size, Easy Maintenance
- 7-digital non-resettable totalizer
- 5-digital sub-total, with floating point from 0.01 to 99999.99
- Horizontally and vertically flexibility of installation options
- Easy to Install, Read & Operate Digital Display
- Low Pressure Drop
- 3.6V lithium battery power, durable service

TECHNICAL SPECIFICATIONS

Model	ASP-E-25	ASP-E-40	ASP-E-50
Size	1" (25mm)	1.5" (40mm)	2" (50mm)
Max Flow Rate	120L/min	250L/min	300L/min
Min Flow Rate	20L/min	25L/min	30L/min
Accuracy	±0.5%	±0.5%	±0.5%
Repeatability	±0.03%	±0.03%	±0.03%
Viscosity Max	1000CPS	1000CPS	1000CPS
Working Pressure	3.4Mpa	1.8Mpa	1.8Mpa
Amount	0~999999.99	0~999999.99	0~999999.99
Volume	0~999999.99	0~999999.99	0~999999.99



sales@asmaindustrial.com
www.asmaindustrial.com

Registered Office / Showroom:
83/85, Netaji Subhas Road, Ground Floor,
Shop No. A30, Kolkata - 700001
Ph No. : 033 22310235

Service Centre :
40, Netaji Subhas Road, Ground Floor,
Kolkata - 700 001, Ph No. : 033 22315080
E-Mail : service@asmaindustrial.com